Printing date 06/04/2020

Version No. 1

Reviewed on 06/04/2020

1 Identification

- Trade name: <u>UZIN NC 890 Hydropatch</u>
- · Application of the substance / the mixture Leveling Compound
- Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Uzin Utz North America Inc. 200 Garrison Oak Dr. Dover, DE 19901 Phone: (302) 450 1108

• Information department: Product safety department email: msds.info@uzin-utz.com

• Emergency telephone number: For Chemical Emergency Spill Leak Fire Exposure or Accident Call CHEMTREC Day or Night: DOMESTIC NORTH AMERICA 800-424-9300 International, call +49 621 60 43 333

2 Hazard(s) identification

· Classification of the substance or mixture

GHS

GHS08 Health hazard

Carc. 1A H350 May cause cancer. Route of exposure: Inhalation.

STOT RE 1 H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.

GHS07

Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H335 May cause respiratory irritation.

· Label elements

- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms GHS05, GHS07, GHS08
- · Signal word Danger

Hazard-determining components of labeling: Portland cement Quartz (crystalline silica)
Hazard statements Causes skin irritation.
Causes serious eye damage.
May cause cancer. Route of exposure: Inhalation.
May cause respiratory irritation.
Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.
Precautionary statements
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe dust.

(Contd. on page 2)

[•] US

Version No. 1

Reviewed on 06/04/2020

Trade name: UZIN NC 890 Hydropatch

Printing date 06/04/2020

(Contd. of page 1)
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin: Wash with plenty of soap and water.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Store in a well-ventilated place. Keep container tightly closed.
Dispose of contents/container in accordance with local/regional/national/international regulations.
· NFPA ratings (scale 0 - 4)
Health = 2
Flammability = 0
2 0 Reactivity = 0
• HMIS-ratings (scale 0 - 4)
$\begin{array}{c c} \text{HEALTH} & 2 \\ \end{array} Health = 2 \end{array}$
FIRE 0 $Flammability = 0$
REACTIVITY 0 Reactivity = 0
Other hazards
NFPA Rating Scale: 0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe.
NFPA is the National Fire Protection Association.
HMIS Rating Scale: 0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe.
HMIS®, the Hazardous Materials Identification System, is a registered mark of the National Paint and
Coatings Association (NPCA).
* Chronic health effect possible - inhalation of silica dust may cause lung injury/disease (silicosis). Take
appropriate measures to avoid breathing dust. See sections 3, 8 and 11.
Results of PBT and vPvB assessment
• <i>PBT:</i> Not applicable.
• vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

•	Hazara	lous	ingre	edients	:
•	Hazara	ous	ingre	edients	j

114441	nazaraous ingrements.		
CAS:			25-50%
		📀 Eye Dam. 1, H318; 🚸 Skin Irrit. 2, H315; STOT SE 3, H335	
			5-<10%
CAS:	14808-60-7	Quartz (crystalline silica)	1-<3%
		🚸 Carc. 1A, H350; STOT RE 1, H372	

• Additional information:

The exact percentages of the ingredients have been withheld by the manufacturer as trade secrets. The amount of respirable cristalline silica is less than 0.1 %.

For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· Description of first aid measures

• After inhalation: Supply fresh air; consult doctor in case of complaints.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 3)

US

Printing date 06/04/2020

Version No. 1

Reviewed on 06/04/2020

(Contd. of page 2)

Trade name: UZIN NC 890 Hydropatch

Call a doctor.

· After swallowing: Do not induce vomiting; immediately call for medical help.

• Information for doctor:

- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

• Extinguishing media

- · Suitable extinguishing agents:
- *CO*₂ extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • *For safety reasons unsuitable extinguishing agents:* Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Wear dust mask. Avoid formation of dust.*
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- *Methods and material for containment and cleaning up: Pick up mechanically.*

Do not flush with water or aqueous cleansing agents

• *Reference to other sections* See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
CAS: 14808-60-7	Quartz (crystalline silica)	$0.075 \ mg/m^3$
CAS: 1305-62-0	calcium dihydroxide	15 mg/m ³
• PAC-2:		
CAS: 14808-60-7	Quartz (crystalline silica)	33 mg/m ³
CAS: 1305-62-0	calcium dihydroxide	240 mg/m ³
• PAC-3:		
CAS: 14808-60-7	Quartz (crystalline silica)	200 mg/m ³
CAS: 1305-62-0	calcium dihydroxide	1,500 mg/m ³

7 Handling and storage

• Handling:

· Precautions for safe handling

Prevent formation of dust.

Wear suitable protective clothing, gloves and eye/face protection.

Avoid contact with the eyes and skin.

When mixing wear suitable NIOSH-approved dust respirator.

Provide appropriate exhaust ventilation at places where airborne dust is generated. In case of insufficient ventilation, wear suitable respiratory protective equipment (e.g. NIOSH-approved dust respirator). Keep away from foodstuffs, beverages and feed.

(Contd. on page 4)

US

Printing date 06/04/2020

Version No. 1

Reviewed on 06/04/2020

Trade name: UZIN NC 890 Hydropatch

(Contd. of page 3)

Wash hands before breaks and at the end of work. • Information about protection against explosions and fires: No special measures required.

· Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: Keep receptacle tightly sealed.

· Information about storage in one common storage facility: Store away from foodstuffs.

· Further information about storage conditions:

Store in dry conditions.

Protect from humidity and water.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems:

Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Ventilation should effectively remove and prevent buildup of any dust generated from the handling of this product.

· Control parameters

· Com	ponents with limit values that require monitoring at the workplace:
	: 65997-15-1 Portland cement
PEL	Long-term value: 50 mppcf or 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	Long-term value: 1* mg/m³ E; *as respirable fraction
CAS	: 7778-18-9 Calcium sulphate
	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	Long-term value: 10* mg/m ³ *as inhalable fraction
CAS	: 14808-60-7 Quartz (crystalline silica)
PEL	Long-term value: 0.05* mg/m ³ *resp. dust; 30mg/m3/%SiO2+2
REL	Long-term value: 0.05* mg/m³ *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m³ *as respirable fraction
· Pers	osure controls onal protective equipment:
	eral protective and hygienic measures: ent formation of dust.
	d contact with the eyes and skin.
	r suitable protective clothing, gloves and eye/face protection.
	away from foodstuffs, beverages and feed.
	h hands before breaks and at the end of work.
	iratory protection:
Prov	n mixing wear suitable NIOSH-approved dust respirator. side appropriate exhaust ventilation at places where airborne dust is generated. In case of insufficient ilation, wear suitable respiratory protective equipment (e.g. NIOSH-approved dust respirator). (Contd. on page 5)
	US

Printing date 06/04/2020

Version No. 1

Reviewed on 06/04/2020

Trade name: UZIN NC 890 Hydropatch

• Protection of hands:



Use nitrile impregnated cotton-gloves

- · Material of gloves Nitrile impregnated cotton-gloves
- · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:

Safety glasses

9 Physical and chemical properties

General Information		
Appearance:		
Form:	Solid	
Color:	Gray	
Odor:	Light Not determined.	
Odor threshold:	Noi determined.	
<i>pH-value at 20 °C (68 °F):</i>	11	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	Undetermined.	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not determined.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure:	Not applicable.	
Density:	Not determined.	
Relative density	Not determined.	
Vapor density	Not applicable.	
Evaporation rate	Not applicable.	
Solubility in / Miscibility with		
Water:	Insoluble.	
	Sets with water.	
Partition coefficient (n-octanol/wat	er): Not determined.	
Viscosity:		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	

(Contd. of page 4)

Printing date 06/04/2020

Version No. 1

Reviewed on 06/04/2020

(Contd. of page 5)

Trade name: UZIN NC 890 Hydropatch

· Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- *Possibility of hazardous reactions* No dangerous reactions known.
- *Conditions to avoid* No further relevant information available.
- *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Specific symptoms in biological assay:
- · Primary route(s) of entry: Inhalation, skin contact, eye contact, ingestion.
- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization:
- No sensitizing effects known.
- Low in Chromate (< 2 ppm) acc. Regulation (EC) No 1907/2006 (REACH).
- Subacute to chronic toxicity:
- The amount of respirable cristalline silica is less than 0.1 %.

Respirable crystalline silica (quartz) may cause a severe lung desease named silicosis. Symptoms of silicosis may be a shortness of breath, fever or cough. Silicosis is reported to increase the risk of carcinogenicity caused by continuous inhalation of respirable crystalline silica. Though the product itself contains less than 0.1% of respirable crystalline silica, respirable silica may be generated from working procedures such as grinding e.g. In general, inhalation of silica dust should be avoided. Therefore, for your own safety wear a suitable NIOSH-approved respirator in all occasions when handling of the product generates dust.

· Additional toxicological information: Carcinogenic.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
CAS: 14808-60-7 Quartz (crystalline silica)	1
· NTP (National Toxicology Program)	
CAS: 14808-60-7 Quartz (crystalline silica)	K
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

• CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) Carc. 1A

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- *Persistence and degradability* No further relevant information available.
- · Behavior in environmental systems:
- $\cdot \textit{Bioaccumulative potential No further relevant information available}.$
- *Mobility in soil* No further relevant information available.

(Contd. on page 7)

US

Printing date 06/04/2020

Version No. 1

Reviewed on 06/04/2020

Trade name: UZIN NC 890 Hydropatch

(Contd. of page 6)

- · Additional ecological information:
- · General notes: Do not allow product to reach ground water, water course or sewage system.

· Results of PBT and vPvB assessment

• *PBT:* Not applicable.

· vPvB: Not applicable.

• Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Do not allow product to reach sewage system.

Mix product residues with water, allow to harden, then dispose of as construction waste.

- · Uncleaned packagings:
- · Recommendation: Empty paper packaging is recyclable.

14 Transport information

· DOT, ADR, ADN, IMDG, IATA	Void
· UN proper shipping name · DOT, ADR, ADN, IMDG, IATA	Void
· DOT, ADN, IMDG, IATA · Class · DOT, IMDG, IATA	Void Void
• Environmental hazards: • Marine pollutant:	No
• Special precautions for user	Not applicable.
• Transport/Additional information	Not regulated as hazardous material according to the above specifications.
· UN "Model Regulation":	Void

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture · SARA (Superfund Amendments and Reauthorization Act)

• EPCRA Section 302 (Extremely Hazardous Substances):

None of the ingredient is listed.

· SARA Title III Section 313 (Toxic Release Inventory - TRI):

None of the ingredients is listed.

• TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65 (California)

Chemicals known to cause cancer:

Crystalline silica (quartz) is classified as a substance known to the State of California to be a carcinogen.

CAS: 14808-60-7 Quartz (crystalline silica)

(Contd. on page 8)

⁻ US

Printing date 06/04/2020

Version No. 1

Reviewed on 06/04/2020

Trade name: UZIN NC 890 Hydropatch

	(Contd. of page
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
Carcinogenicity categories	
EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
TLV (Threshold Limit Value established by ACGIH)	
CAS: 14808-60-7 Quartz (crystalline silica)	A
NIOSH-Ca (National Institute for Occupational Safety and Healt	(h)
CAS: 14808-60-7 Quartz (crystalline silica)	
Hazard pictograms GHS05, GHS07, GHS08 Signal word Danger	
Hazard-determining components of labeling: Portland cement	
<i>Quartz (crystalline silica)</i>	
Hazard statements	
Causes skin irritation.	
Causes serious eye damage.	
May cause cancer. Route of exposure: Inhalation.	
May cause respiratory irritation.	
Causes damage to the lung through prolonged or repeated exposur	e. Route of exposure: Inhalation.
Precautionary statements Obtain special instructions before use.	
Do not handle until all safety precautions have been read and unde	rstood
Do not handle unit all sujety precautions have been read and ande Do not breathe dust.	151004.
Wear protective gloves/protective clothing/eye protection/face protection	ection.
If on skin: Wash with plenty of soap and water.	
If in eyes: Rinse cautiously with water for several minutes. Remove Continue rinsing.	e contact lenses, if present and easy to
IF exposed or concerned: Get medical advice/attention.	
If eye irritation persists: Get medical advice/attention.	
Store in a well-ventilated place. Keep container tightly closed.	
Dispose of contents/container in accordance with local/regional/na	ttional/international regulations.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Contact:

Jim Muggleton Phone: +1 720-374-4810 Mobile: +1 720-413-5454

• Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 9)

Printing date 06/04/2020

Version No. 1

Reviewed on 06/04/2020

Trade name: UZIN NC 890 Hydropatch

DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Carc. 1A: Carcinogenicity - Category 1A STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

(Contd. of page 8)